



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|--|-------------|----------------------|---------------------|------------------|
| 10/826,941 | 04/17/2004 | Charles D. Kim | EMP-140US | 1621 |
| 24314 | 7590 | 08/11/2005 | EXAMINER | |
| JANSSON, SHUPE & MUNGER & ANTARAMIAN, LTD 245 MAIN STREET RACINE, WI 53403 | | | GUADALUPE, YARITZA | |
| | | | ART UNIT | PAPER NUMBER |
| | | | 2859 | |

DATE MAILED: 08/11/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

| | | | |
|------------------------------|---|--|--|
| Office Action Summary | Application No. 10/826,941 | Applicant(s) KIM, CHARLES D. | |
| | Examiner Yaritza Guadalupe McCall | Art Unit 2859 | |

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 24 May 2005.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-19 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-19 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152..

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

In response to Amendment filed May 24, 2005

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1 – 3, 6 – 9 and 12 – 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kohner (US 5,709,034) in view of Baker et al. (US 5,406,714).

In regards to claim 1, Kohner discloses a device which will allow to achieve the step of mounting a vial (32, 90) in a level (12) providing for increased visibility of the vial, the method comprising the step of providing the level (12) with a recess (56) and a measuring surface (14, 16); positioning the vial (90) in the recess (56) at an angular relationship (perpendicular to the measuring surfaces as shown in Figure 1) to the measuring surface; and enclosing the vial within the recess with a ring member (20, 40), the ring member comprising front and rear portions (See Figure 2) having a circular configuration and with the vial positioned therebetween (See Figure 5).

With respect to claim 2, Kohner also discloses a device wherein the ring member (20) is a first ring member with first front and rear portions (See Figure 2), the method further comprising enclosing the first ring member with a second ring member having front and rear portions.

In regards to claim 3 : Kohner teaches a device having ring members (40, 44, 48) having front and rear portions (as shown in Figure 2) and also provided with wing members (46) having apertures (49). Kohner discloses an alternate arrangement for securing the vial in place which uses said apertures (49) of the wing members in cooperation with fasteners / ribs (74) provided on a securing cap (30) which will receive and retain the vial in fixed relationship to the device by securing the first and second ring members to the level (See Column 4, lines 12 – 26) and finally receiving the vial once the rings member is secured within said securing cap (30).

In regards to the method step as stated in claim 6, Kohner teaches a device wherein the first and second ring members (20, 40, 44) are bonded together before the vial is enclosed in the recess (See Figure 3 and Column 3, lines 18 – 26).

Regarding claim 7, Kohner discloses a level (12) having a vial (32, 90) secured thereto, the level comprising a body (12) having a measuring surface (14, 16) and a recess (56); a vial (32, 90) positioned in the recess at an angular relationship (i.e., perpendicular) to the

measuring surface (14, 16); and a ring member (40, 44, 48) enclosing the vial within the recess (56), the ring member (40, 44, 48) comprising front and rear portions being circular (as defined by the cylindrical ring # 44) with the vial positioned therebetween.

With respect to claim 8, Kohner further discloses the ring member (40, 44, 48) being a first ring member with first ring member portions, the level further comprising a second ring member enclosing the first ring member, the second ring member having front and rear portions (See Figure 2).

In regards to claims 9 and 15, Kohner discloses a level wherein the second portions include wing members (46) having apertures (49) therein, the apertures receiving fasteners to secure the second ring member to the level. Kohner discloses an alternate arrangement for securing the vial in place which uses said apertures (49) of the wing members in cooperation with fasteners / ribs (74) provided on a securing cap (30) which will receive and retain the vial in fixed relationship to the device by securing the first and second ring members to the level (See Column 4, lines 12 – 26) and finally receiving the vial once the rings member is secured within said securing cap (30).

With respect to claim 12, Kohner teaches a device wherein the first and second ring members are bonded together (See Figure 3) prior to receiving the vial (32, 90).

Regarding claim 13, Kohner discloses a level having a vial secured thereto, the level comprising a body (12) having a measuring surface (14, 16) and a recess (56); a vial (32, 90) positioned in the recess (56) at an angular relationship, i.e. perpendicular, to the measuring surface (14, 16); and a ring member (40, 44, 48) being circular and enclosing the vial within the recess, the ring member engaging the vial (32, 90) and the body (12), whereby the vial is protected by the level and ring member while visibility of the vial is enhanced.

In regards to claim 14, Kohner discloses the vial (32, 90) including a central portion where a bubble rests when the measuring surface is at a desired orientation, said portion defined by the two center parallel lines where the bubble (34) is retained within as shown in Figure 5.

Kohner does not disclose the first and second portions of the ring member having beveled edges forming a funnel-shaped surface as stated in claims 1 – 2, 7 – 8 and 13, and wherein said slope line intersects the central portion as stated in claim 14.

With respect to the beveled edges as stated in claims 1 – 2, 7 – 8 and 13 - 14 : Baker et al. discloses a level vial assembly having a level (10) provided with a recess (20, 24) for receiving a pair of vials (36), and enclosing the vials with ring members (30) having beveled edges (66) forming a funnel-shaped surface defining slope lines that intersect the vial, in order to help increase the visibility of the vials during use. Therefore, it would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify the device

disclosed by Kohner by providing beveled edges to the outer edges of the ring members as taught by Baker et al. in order to help increase the visibility of the vials during use.

3. Claims 4, 10 and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kohner (US 5,709,034) in view of Baker et al. (US 5,406,714), as applied to claims 1 – 3, 6 – 9, 12 – 13 and 15 above, and further in view of Macdermott et al. (US 4,407,075).

Kohner and Baker et al. disclose a device as stated in paragraph 2 above.

Kohner and Baker et al. do not disclose the first and second ring members having contrasting colors to outline the vial as stated in claims 4, 10 and 16.

With respect to claims 4, 10 and 16 : Kohner and Baker disclose a device having a vial (32, 90) received within a first and second ring member (40, 44, 48) but do not disclose the particular color of these members. MacDermott et al. discloses, as part of its background of the invention, the problems encountered by construction workers or any user when reading bubble vials provided on level devices. MacDermott et al. identifies poor lighting and dark color working surfaces as impediments to the user to accurately read a bubble vial. For these reasons, and in an attempt to enhance or intensify the bubble image, the use of luminescent, reflective or color contrasting backgrounds are used when constructing a level device (See Column 1, lines 21 – 39 of MacDermott et al.). Therefore, it would have been obvious to a person having

ordinary skill in the art at the time the invention was made to modify the ring members disclosed b Kohner and Baker by providing contrasting colors on said first and second ring members as taught by MacDermott et al. in order to outline the vial and enhance and intensify the bubble image at any type of lighting conditions.

4. Claims 5, 11, 14 and 17 – 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kohner (US 5,709,034) in view of Baker et al. (US 5,406,714) in view of Macdermott et al. (US 4,407,075), as applied to claims 1 – 4, 6 – 10, 12 – 13, and 15 – 16 above, and further in view of Kivisto et al. (US Pub. No. 2002/0186123)

Kohner, Baker et al., and MacDermott et al. disclose a device as stated in paragraphs 2 and 3 above.

Kohner, Baker et al. and MacDermott et al. do not disclose the ring member having a soft elastomeric providing impact absorption to the level as stated in claim 5, 11, 14, and 17 – 19.

In regards to the soft elastomeric as stated in claims 5, 11 and 17 – 19 : Kohner, Baker et al. and MacDermott et al. discloses a level device having first and second ring members (40, 44, 48 of Kohner) for securing and protecting the level vials and provided with a resilient strip (42), but the particular material has not been disclosed.

Kivistos et al. discloses an apparatus provided with a housing (12) made of an elastomeric, lightweight and corrosion resistant material such as acrylonitrile butadiene-styrene (ABS) (See paragraph [0024], lines 12 – 16), a material with a density of 1.05 (See table attached in Appendix A below and obtained from www.polymerweb.com), and also gives the option of utilizing a seal assembly (36) made of thermoplastic rubber, which has a density of 0.92 (See table attached in Appendix B below and obtained from www.azom.com), lower than that of ABS, in order to provide a tight seal that resists the entry of liquids or gases (See paragraph [0026], lines 10 – 15) and since ABS and thermoplastic rubber materials are well known types of soft elastomeric materials which will provide impact absorption due to their elastomeric properties, and since Webster's Dictionary 10th Edition defines elastomeric as “any of various elastic substances resembling rubber”, and Kivistos et al. already teaches the need and convenience of utilizing thermoplastic rubber as the material for the seal assembly.

Therefore, it would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify the device disclosed by Kohner, Baker et al. and MacDermott et al. by making the second ring member out of acrylonitrile butadiene-styrene (ABS) with an outer layer of thermoplastic rubber in order to provide an elastomeric, lightweight and corrosion resistant material (See Kivistos et al. paragraph [0024], lines 12 – 16) and in order to provide a tight seal that resists the entry of liquids or gases (See Kivistos et al. paragraph [0026], lines 10 – 15) which will result in prolonging the life span of the device.


APPENDIX A

ABS Acrylonitrile Butadiene Styrene

LEGEND

A = amorphous - Cr = crystalline - C = clear - E = excellent - G = good - P = poor - O = opaque - T = translucent - R = Rockwell - S = Shore

STRUCTURE: A



SPECIFIC DENSITY: 1.05

WATER ABSORPTION RATE (%): 0.27

ELONGATION (%): 20

TENSILE STRENGTH (psi): 4300

COMPRESSION STRENGTH (psi): 9000

FLEXURAL STRENGTH (psi): 9200

FLEXURAL MODULUS (psi): 300000

IMPACT (IZOD ft. lbs/in): 6.6

HARDNESS: R110

FABRICATION

- BONDING: E
- ULTRASONIC WELDING: E
- MACHINING: G

DEFLECTION TEMPERATURE (deg. F)

- @ 66 psi: 206
- @ 264 psi: 193

UTILIZATION TEMPERATURE (deg. F)

- min: -40
- max: 194

MELTING POINT (deg. F): 221



COEFFICIENT OF EXPANSION: 0.000053

ARC RESISTANCE: 80

DIELECTRIC STRENGTH (kV/mm): 16

TRANSPARENCY: T

APPENDIX B



Low Density Polyethylene - LDPE

Polymer Type

Thermoplastic

← Material

Advantages

Cheap, good chemical resistance. High impact strength at low temperatures. Excellent electrical properties. Can be processed by all conventional methods. Can be transparent in thin film form.

Disadvantages

Low strength, stiffness and maximum operating temperature. Flammable. Poor UV resistance. High gas permeability (particularly CO_2). Susceptible to environmental stress cracking.

Typical Properties

| Property | Value |
|--|--------|
| Density (g/cm^3) | 0.92 |
| Surface Hardness | SD48 |
| Tensile Strength (MPa) | 10 |
| Flexural Modulus (GPa) | 0.25 |
| Notched Izod (kJ/m) | 1.06+ |
| Linear Expansion ($^{\circ}\text{C} \times 10^{-5}$) | 20 |
| Elongation at Break (%) | 400 |
| Strain at Yield (%) | 19 |
| Max. Operating Temp. ($^{\circ}\text{C}$) | 50 |
| Water Absorption (%) | 0.01 |
| Oxygen Index (%) | 17 |
| Flammability UL94 | HB |
| Volume Resistivity (log ohm.cm) | 16 |
| Dielectric Strength (MV/m) | 27 |
| Dissipation Factor 1kHz | 0.0003 |
| Dielectric Constant 1kHz | 2.3 |
| HDT @ 0.45 MPa ($^{\circ}\text{C}$) | 50 |
| HDT @ 1.80 MPa ($^{\circ}\text{C}$) | 35 |
| Material. Drying hrs @ ($^{\circ}\text{C}$) | NA |

Low Density Polyethylene - LDPE

Page 2 of 2

| | |
|--------------------------|-----------|
| Melting Temp. Range (°C) | 220 - 260 |
| Mould Shrinkage (%) | 3 |
| Mould Temp. Range (°C) | 20 - 40 |

Applications

Chemically resistant fittings, bowls, lids, gaskets, toys, containers, packaging film, film liners, squeeze bottles. Heat-seal films for metal laminates. Pipe, cable covering, core in UHF cables.

Source : Abstracted from Plascams
For more information on Plascams please visit
[RAPRA Technology Ltd.](#)

particular
characteristics
of thermoplastic
MATERIALS



Response to Arguments

5. Applicant's arguments filed May 24, 2005 have been fully considered but they are not persuasive.

With respect to the ring member being circular and having beveled edges forming a funnel shaped surface, it is pointed out that the structure shown by the combination of Kohnrr and Baker clearly meets the requirements of the claimed subject matter. It is further noted, that although the claims are commonly interpreted in light of the specification and the knowledge of an artisan in the art for clarity and understanding, these interpretations cannot be brought into the claim language. Therefore, Applicant is reminded that arguing features that are being transported into the claims without being actually claimed is improper. During examination of the application, the claims are given their broadest interpretation and the use of the specification and dictionaries are only a mechanism of clarification of a term, not to transport all their contents into the claim language.

In a broad sense, the ring member disclosed by Kohner and Baker meet the structural requirements of the claimed subject matter, such as a front and rear portions with the vial positioned therebetween, said portions being circular and having beveled edges (66) forming a funnel-shaped surface. The beveled surfaces (66) of Baker clearly form a funnel – shaped surface. ADD change of shape PAR.

The rationale for the combination of Kohner and Baker was clearly established by the need of the user to have a wide range of visibility of the window. By providing beveled surfaces, the visibility of the vial will increase, as the user would be able to see the vial at different orientations, versus having a straight surface, which would require the user to be directly facing the window. Meeting a need, is sufficient basis for establishing a motivation statement for a particular combination.

Conclusion

6. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).


A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Yaritza Guadalupe McCall whose telephone number is (571)272-2244. The examiner can normally be reached on 8:00 AM - 5:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Diego F.F. Gutierrez can be reached on (571) 272-2245. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Yaritza Guadalupe-McCall
Patent Examiner
Art Unit 2859
August 8, 2005



CHRISTOPHER W. FULTON
PRIMARY EXAMINER